

APS 007 mobile unit for loading solar thermal system

Technical description

APS007 is designed to quickly loading and washing solar plants with use of products based on glycol. The machine combines the washing function of solar system with the loading function and pressurizing them, using a high prevalence vane pump.

The appliance isn't suitable to work with alimentary and aggressive fluid.

The machine is supplied fully assembled and wired: it is hydraulically and electrically tested.

Raccomanded application

Washing and cleaning solar thermal system used in maintenance and riqualification plants


Washing and prezzurizing solar thermal system with use products based on ethylene glycol.

General technical data

PE tank	: 30 lt.
Capacity pump	: 27 lt./min
Type of pump	: vane pump
MAX prevalence	: 8,8 bar
Integrated by-pass pump	: settable
Electrical protection pump	: IP 45

Hydraulic couplings diam	: 3/4"
Manometro diam. 63 mm B. glicerina	: sc. 0-16 bar
MIN temperature glycol fluid	: -5° C.
MAX temperature glycol fluid	: 35° C.
Mains supply	: 230 V.50 Hz

Flow chart/prevalence




Direzione amministrativa e commerciale

Via Del Parco, 5
20080 Albairate (MI) Italia
Tel (+039) 02.94061133
Fax (+039) 02.94061133

Produzione e laboratorio


Via E. Toti, 32
20080 Albairate (MI) Italia
Tel (+039) 02.94921122
Fax (+039) 02.94921122

APS 007 mobile unit for loading solar thermal system



Description of the main components installed

- 1- Metal frame painted
- 2- Polyethylene tank 30 lt
- 3- Return Shut-off valve
- 4- Vane pump
- 5- Network attack with gasket
- 6- Supply Shut-off valve
- 7- Pressure gauge



Direzione amministrativa e commerciale

Via Del Parco, 5
20080 Albairate (MI) Italia
Tel (+039) 02.94061133
Fax (+039) 02.94061133

Produzione e laboratorio

Via E. Toti, 32
20080 Albairate (MI) Italia
Tel (+039) 02.94921122
Fax (+039) 02.94921122